

Drain systems

Drain enzyme/Bacteria pump

seko, an industry leading manufacturer of timed dosing systems introduces a new battery powered drain dosing system. **seko's** state of the art electronics and industry experience insures reliability and ease of use.



Transaxle Technology provides added support and stability to the gear shaft.

This equalizes roller pressure, extending the life of the motor gearbox and squeeze tube.



Drain Plus



Drain Battery



Drain Plus Perfect control



Drain Plus is the industry's leading drain chemical dispenser. Drain Plus offers unsurpassed reliability and durability in the field.

RELIABILITY

- With the new microprocessor the system automatically recognizes input voltage and accepts 100VAC to 240VAC
- The digital display counts down dosing time providing visual verification
- Nema 4X enclosure

EASY

- Easy installation
- Easy and intuitive with two separate menus for settings and programming
- Dosing time can be digitally set or measured by calibration
- Variable pump speed
- Option to set output by programming units of measure
- Easy to see blue backlight display

ADAPTABILITY

- Automatic switching to accept 100 – 240 VAC
- Pump speed regulation capability
- Set up to 48 daily dosing operations
- Outputs for optional external empty product alarm
- Installation kit suitable for most typical institutional applications

GENERAL FEATURES

Part number:	SDRPL7PM3000
Power supply:	100 - 240VAC
NO. of feeds/24h max:	48
Flow Rate:	Adj 120 ml/h to 12 l/h (0.07 oz/min to 6.8 oz/min)
Relay function:	Pump After/before-alarm
Note:	Intallation kit included

Drain Battery With extended battery life



Suitable for a wide range of applications requiring timed dosing, most notably, grease trap treatment in restaurants, grocery store meat departments, meat processing and packing facilities and lift station treatment.

RELIABILITY

- Industry standard timer for intuitive programming of up to 17 dosings per day and up to 7 days per week.

EXTENDED BATTERY LIFE

- Dual lantern batteries combined with low consumption motor offer actual pump run time in excess of 50 hours on one set of batteries.

DURABILITY

- Peristaltic pump with transaxle technology and Sekoflex tube provide excellent chemical compatibility and resistance to mechanical wear.



GENERAL FEATURES

Part number:	SDRBT8PF3000
Power supply:	12VDC
NO. of feeds/24h max:	17
Flow Rate:	6 lt/h 3.5 oz/min
Note:	Installation kit ready for the most common installations